


21.151

CE



Feature: Safety BNC Male with 2x4mm Male Safety Socket
Material:
Body: Brass; Surface: Nickel plated
Rating: CAT I 500V, CAT II 150V/3A




21.152

CE



Feature: Safety BNC Male with 2x4mm Female Safety Socket
Material:
Body: Brass; Surface: Nickel plated
Rating: CAT I 500V, CAT II 150V/3A



27.187.*




材质 Material
绝缘 Insulator: PA
主体 Body: 铜 Brass
表面 Surface: 镀镍 Nickel plated
电气性能 Rated voltage/current
30Vac-60Vdc/Max.10A



27.260.*




材质 Material
绝缘 Insulator: PA
主体 Body: 铜 Brass
表面 Surface: 镀镍 Nickel plated
电气性能 Rated voltage/current
CAT III 300V/Max.15A



27.257.*




材质 Material
绝缘 Insulator: PA
主体 Body: 铜 Brass
表面 Surface: 镀镍 Nickel plated
电气性能 Rated voltage/current
CAT II 300V/Max.15A



27.262.*




材质 Material
绝缘 Insulator: PA
主体 Body: 铜 Brass
表面 Surface: 镀镍 Nickel plated
电气性能 Rated voltage/current
CAT III 1000V/Max.32A



27.258.*




材质 Material
绝缘 Insulator: PA
主体 Body: 铜 Brass
表面 Surface: 镀镍 Nickel plated
电气性能 Rated voltage/current
CAT II 300V/Max.15A



27.263.*




材质 Material
绝缘 Insulator: PA
主体 Body: 铜 Brass
表面 Surface: 镀镍 Nickel plated
电气性能 Rated voltage/current
CAT III 1000V/Max.32A



27.259.*



材质 Material
绝缘 Insulator: ABS
主体 Body: 钢 Steel
表面 Surface: 镀镍 Nickel plated
电气性能 Rated voltage/current
30Vac-60Vdc/Max.19A



27.264.*



材质 Material
绝缘 Insulator: PA
主体 Body: 铜 Brass
表面 Surface: 镀镍 Nickel plated
电气性能 Rated voltage/current
CAT III 1000V/Max.32A

