


25.401.*




材质 Material
 绝缘 Insulator: ABS
 主体 Body: 铜 Brass
 弹片 Spring: 铍铜 Beryllium copper
 表面 Surface: 镀镍 Nickel plated
 * 螺丝压接 Screw connection
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.24A



25.402.*




材质 Material
 绝缘 Insulator: ABS
 主体 Body: 铜 Brass
 弹片 Spring: 磷铜 Phosphorus copper
 表面 Surface: 镀镍 Nickel plated
 * 焊接 Solder connection
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.19A



25.403.*




材质 Material
 绝缘 Insulator: PE
 主体 Body: 铜 Brass
 弹片 Spring: 铍铜 Beryllium copper
 表面 Surface: 镀镍 Nickel plated
 * 螺丝压接 Screw connection
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.32A



25.404.*




材质 Material
 绝缘 Insulator: ABS
 主体 Body: 铜 Brass
 弹片 Spring: 铍钢 Steel
 表面 Surface: 镀镍 Nickel plated
 * 螺丝压接 Screw connection
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.32A



25.405.*




材质 Material
 绝缘 Insulator: ABS
 主体 Body: 铜 Brass
 弹片 Spring: 铍钢 Steel
 表面 Surface: 镀金 Gold plated
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.24A



25.410.*




材质 Material
 绝缘 Insulator: PVC
 主体 Body: 铜 Brass
 弹片 Spring: 钢 Steel
 表面 Surface: 镀镍 Nickel plated
 * 螺丝压接 Screw connection
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.24A



25.411.*




材质 Material
 绝缘 Insulator: PVC
 主体 Body: 铜 Brass
 弹片 Spring: 铍铜 Beryllium copper
 表面 Surface: 镀镍 Nickel plated
 * 螺丝压接 Screw connection
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.24A



25.412.*




材质 Material
 绝缘 Insulator: PVC
 主体 Body: 铜 Brass
 弹片 Spring: 铍铜 Beryllium copper
 表面 Surface: 镀镍 Nickel plated
 * 螺丝压接 Screw connection
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.24A



25.413.*




材质 Material
 绝缘 Insulator: PVC
 主体 Body: 铜 Brass
 弹片 Spring: 磷铜 Phosphorus copper
 表面 Surface: 镀镍 Nickel plated
 * 螺丝压接 Screw connection
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.32A



25.414.*




材质 Material
 绝缘 Insulator: PVC
 主体 Body: 铜 Brass
 表面 Surface: 镀镍 Nickel plated
 * 螺丝压接 Screw connection
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.32A



25.415.*



材质 Material
 绝缘 Insulator: PVC
 主体 Body: 铜 Brass
 表面 Surface: 镀镍 Nickel plated
 * 螺丝压接 Screw connection
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.24A



25.416.*




材质 Material
 绝缘 Insulator: PVC
 主体 Body: 铜 Brass
 弹片 Spring: 铍铜 Beryllium copper
 表面 Surface: 镀镍 Nickel plated
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.32A



25.418.*




材质 Material
 绝缘 Insulator: ABS
 主体 Body: 铜 Brass
 弹片 Spring: 铍钢 Steel
 表面 Surface: 镀金 Gold plated
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.32A



25.419.*




材质 Material
 绝缘 Insulator: ABS
 主体 Body: 铜 Brass
 弹片 Spring: 铍钢 Steel
 表面 Surface: 镀金 Gold plated
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.32A



25.420.*



材质 Material
 绝缘 Insulator: ABS
 主体 Body: 铜 Brass
 表面 Surface: 镀金 Gold plated
 * 螺丝压接 Screw connection
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.24A



25.422.*



材质 Material
 绝缘 Insulator: PA
 主体 Body: 铜 Brass
 弹片 Spring: 铍铜 Beryllium copper
 表面 Surface: 镀镍 Nickel plated
 * 焊接 Solder connection
 电气性能 Rated voltage/current
 30Vac-60Vdc/Max.24A

